

PART 1 - GENERAL

1.01 DESCRIPTION OF WORK

- A. This section includes sliding door, wall mounted display cases with wood frame

1.02 REFERENCED STANDARDS

- A. ASTM-E 84
- B. ASTM B221

1.03 SUBMITTALS

- A. Shop Drawings: Provide shop drawings for each wall mounted display case, as required.
- B. Product Data: Provide technical data for materials specified. Include Material Safety Data Sheets, when applicable.
- C. Samples:
 - 1. Manufacturer's color charts
 - 2. Composition samples of material and trim to illustrate finish, color and texture.

1.04 OPERATION & MAINTENANCE

- D. Include data on regular cleaning, stain removal, and precautions.

1.05 REGULATORY REQUIREMENTS

- A. Conform to applicable code for flame/smoke rating in tackboards in accordance with ASTM-E 84.

1.06 QUALITY ASSURANCE

- A. Provide all items in this section as provided by:
 - WIUSA.com
 - PO Box 567949
 - Dallas, TX 75356
 - Phone: 800-527-9014; Fax: 214-631-4654
 - www.wiusa.com
 - sales@wiusa.com

1.07 FIELD CONDITIONS

- A. Field measure prior to preparation of shop drawings and fabrication to ensure proper fit.

1.08 WARRANTY

- A. Submit a standard warranty, stating when installed in accordance with manufacturer's instructions and recommendations, Claridge wood frame, wall mounted display cases are guaranteed for one year against defects in materials and workmanship. Guarantee does not cover normal wear and tear, improper handling, any misuse, or any defects caused by vandalism or subsequent abuse. Guarantee covers replacement of defective material but does not include cost of removal or reinstallation.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. 390 Series Large Door Display Cases as manufactured by: Claridge Products and Equipment, Inc., as provided by WIUSA.com, PO Box 567949, Dallas, TX 75356, 800-527-9014, FAX: 214-631-4654, www.wiusa.com, sales@wiusa.com.

2.02 MATERIALS

- A. No. 309 Wall Mounted Sliding Door Display Case
 - 1. Select from back panels of Claridge Cork, Fabricork, Hook-Fab, Designer Fabric or low-pressure laminate with walnut or oak grain finish
 - 2. Standard sizes:

DIVISION 10 - SECTION 10100 / DIVISION 12 - SECTION 12350

- a. 7" depth - 36" x 48", 48" x 60" and 48" x 72"; inside cabinet depth is 5-1/8"
 - b. 10-3/4" depth - 48" x 60" and 48" x 72"; inside cabinet depth is 8-7/8" (10-3/4" deep cases have center mullion for added support.)
3. Housing: Perimeter trim is clear red oak in natural, medium or dark finish
- A. Glass Doors: Glass doors are 3/16" tempered, unless otherwise specified.
 1. Sliding door cases have ground-in finger pulls, doors slide on glides, and are fitted with flat key tumbler locks
 - B. Metal Trim and Accessories: Provide aluminum extrusions as manufactured by Claridge Products and Equipment, Inc. Trim shall be heavy gauge extruded aluminum and shall meet or exceed ASTM B221 Alloy Standards. All aluminum components are finished with bronze finish.
 - C. Colors: As selected from manufacturer's standard colors. Claridge Cork, Fabricork, Designer Fabric, Hook-Fab and walnut or oak grain low-pressure laminate finish available. Over 50 standard tackboard colors to choose from. Color charts furnished on request.
 - D. Hanging Devices: Angle hangers furnished continuous top and bottom.
 - E. Options: Fluorescent lights, genuine walnut wood with natural or oil finish; mahogany with natural or stain finish; maple with natural finish; or cherry with stain finish. Wood finish color charts furnished on request.

2.03 FABRICATION

- A. Shop assembly: Provide factory assembled cases to requirements indicated on shop drawings.
- B. Units shall be of dimensions shown in details or in accordance with manufacturer's shop drawings, as approved by architect.

PART 3 - EXECUTION

3.01 PROJECT CONDITIONS

- A. Verify before installation that interior moisture and temperature approximate normal occupied conditions.
- B. Verify that wall surfaces are prepared and ready to receive units.

3.02 INSTALLATION

- A. Deliver factory built units completely assembled in one piece without joints, wherever possible.
- B. Follow manufacturer's instructions for storage and handling of units before installation.
- C. Install level and plumb, with fasteners furnished, in accordance with manufacturer's recommendations.

3.03 ADJUST AND CLEAN

- A. Verify that all accessories are installed as required for each unit.
- B. At completion of work, clean glass surfaces, tackboard panels and trim in accordance with manufacturer's recommendations, leaving all materials ready for use.